html 5 — Visual Cheat Sheet

<!-- --> — none
comment

<!DOCTYPE> — none
document type

<a> — charset, coords, href, hreflang, media, name, ping, rel, rev, shape, target, type
hyperlink

<abbr> — g
abbreviation

<acronym> — Not supported in HTML 5, use <abbr> instead
acronym

<address> — g
address element

<applet> — Not supported in HTML 5, use <object> instead
applet

<area> — alt, coords, href, hreflang, nohref, media, ping, rel, shape, target, type
image map area

<article> — g
article

<aside> — g
content aside from the page content

<audio> — autoplay, controls, end, loopend, loopstart, playcount, src, start
sound content

<b> — g
bold text

<base> — href, target
base URL for all the links in a page

<basefont> — Not supported in HTML 5, use CSS instead
base font

<bdo> — dir
text direction

<big> — Not supported in HTML 5, use CSS instead
big text

<blockquote> — cite
long quotation

<body> — g
body element

**
** — g
single line break

<button> — autofocus, disabled, name, type, value
push button

<canvas> — height, width
graphics

<caption> — g
table caption

<center> — Not supported in HTML 5, use CSS instead
centered text

<cite> — g
citation

<code> — g
code text

<col> — align, char, charoff, span, valign, width
attributes for columns

<colgroup> — align, char, charoff, span, valign, width
groups of columns

<command> — checked, default, disabled, hidden, icon, label, radiogroup, type
command button

<datagrid> — disabled, multiple
data in a tree-list

<datalist> — data
dropdown list

<datatemplate> — g
data template

<dd> — g
definition description

<del> — cite, datetime
deleted text

<details> — open
details of an element

<dialog> — g
dialog (conversation)

<dir> — Not supported in HTML 5, use CSS instead
directory list

<div> — g
section in a document

<dfn> — g
definition term

<dl> — g
definition list

<dt> — g
definition term

<em> — g
emphasized text

<embed> — height, src, type, width
embedded content

<event-source> — src
target for events sent by a server

<fieldset> — disabled, form
fieldset

<figure> — g
group of media content

<font> — Only the style attribute is supported in HTML 5. Use CSS instead
text font, size, and color

<footer> — g
footer for a section or page

<form> — action, data, replace, accept, accept-charset, enctype, method, name, target
form

<frame> — Not supported in HTML 5
sub window

<frameset> — Not supported in HTML 5
set of frames

<h1> - <h6> — align
header 1 to header 6

<head> — profile
document information

<header> — g
header for a section or page

<hr> — align, noshade, size, width
horizontal rule

<html> — manifest, xmlns
html document

<i> — g
italic text

<iframe> — align, frameborder, height, longdesc, marginheight, marginwidth, name, scrolling, src, width
inline sub window

<img> — alt, src, align, border, height, hspace, ismap, longdesc, usemap, vspace, width
image

<input> — accept, align, alt, autocomplete, autofocus, checked, disabled, form, inputmode, list, max, maxlength, min, name, pattern, readonly, replace, required, size, src, step, template, type, value
input field

<ins> — cite, datetime
inserted text

<isindex> — Not supported in HTML 5
single-line input field

<kbd> — g
keyboard text

<label> — for
label for a form control

<legend> — align
title in a fieldset

<li> — type, value
list item

<link> — charset, href, hreflang, media, rel, rev, target, type
resource reference

<mark> — g
marked text

<map> — id, name
image map

<menu> — autosubmit, compact, label, type
menu list

<meta> — charset, content, http-equiv, name, scheme
meta information

<meter> — high, low, max, min, optimum, value
measurement within a predefined range

<nav> — g
navigation links

<nest> — filter, mode
nestingpoint in a datatemplate

<noframes> — Not supported in HTML 5
noframe section

<noscript> — none
noscript section

<object> — align, archive, border, classid, codebase, codetype, data, declare, height, hspace, name, standby, type, usemap, vspace, width
embedded object

<ol> — compact, start, type
ordered list

<optgroup> — label, disabled
option group

<option> — disabled, label, selected, value
option in a drop-down list

<output> — form
types of output

<p> — align
paragraph

<param> — name, type, value, valuetype
parameter for an object

<pre> — width
preformatted text

<progress> — max, value
progress of a task of any kind

<q> — cite
short quotation

<rule> — condition, mode
rules for updating a template

<s> — Not supported in HTML 5, use CSS instead
strikethrough text

<samp> — g
sample computer code

<script> — async, type, charset, defer, language, src
script

<section> — g
section in a document

<select> — autofocus, data, disabled, form, multiple, name, size
selectable list

<small> — g
small text

<source> — media, src, type
media resources

<span> — g
section in a document

<strike> — Not supported in HTML 5, use CSS instead
strikethrough text

<strong> — g
strong text

<style> — media, scoped, type
style definition

<sub> — g
subscripted text

<sup> — g
superscripted text

<table> — align, bgcolor, border, cellpadding, cellspacing, frame, rules, summary, width
table

<tbody> — g
table body

<td> — abbr, align, axis, bgcolor, char, charoff, colspan, headers, height, nowrap, rowspan, scope, valign, width
table cell

<textarea> — autofocus, cols, disabled, form, inputmode, name, readonly, required, rows
text area

<tfoot> — g
table footer

<th> — abbr, align, axis, bgcolor, char, charoff, colspan, headers, height, nowrap, rowspan, scope, valign, width
table header

<thead> — g
table header

<time> — datetime
date/time

<title> — g
document title

<tr> — align, bgcolor, char, charoff, valign
table row

<tt> — Not supported in HTML 5, use CSS instead
teletype text

<u> — Not supported in HTML 5, use CSS instead
underlined text

<ul> — compact, type
unordered list

<var> — g
variable

<video> — autoplay, controls, end, height, loopend, loopstart, playcount, poster, src, start, width
video

<xmp> — Not supported in HTML 5
preformatted text