



Apache Quick Reference Card

Revision 1.6 for Apache version 1.3.6

Andrew Ford refcards.com™






This card summarizes information in the Apache documentation, which can be found at <http://www.apache.org/docs/>.

Each directive is listed with its arguments. Defaults are given where appropriate in parentheses at the end of the line, followed by an indication of the status of the directive (C – core, B – base, E – extension) and the contexts in which the directive is valid (c – in a configuration file, v – within a virtual host section, d – within a directory section, a – in an access control file).







Options and directives that are new for Apache 1.3 are marked , while those that have changed are marked .

Command line options

httpd [-d *directory*] [-f *file*] [-C *directive*]
[-c *directive*] [-L] [-l] [-S] [-v] [-V] [-X]







- d *directory* initial value for ServerRoot
- D *parameter* define parameter for <IfDefine>
- f *file* configuration file (conf/httpd.conf)
- C *directive* process *directive* before reading config files 
- c *directive* process *directive* after reading config files 
- L list available configuration directives and exit 
- l list compiled-in modules and exit 
- S show *vhos*t settings
- t test syntax of configuration files and exit
- v print version and build date, and exit
- V show compilation settings and exit 
- X single-process debug mode

General configuration directives






DocumentRoot <i>directory</i>	(/usr/local/apache/htdocs)	C cv
ServerRoot <i>directory</i>	(/usr/local/apache)	C c
AccessConfig <i>filename</i>	(conf/access.conf)	C cv
ResourceConfig <i>filename</i>	(conf/srm.conf)	C cv
Include <i>filename</i>		C cvd 
TypesConfig <i>filename</i>	(conf/mime.types)	B c
PidFile <i>filename</i>	(logs/httpd.pid)	C c
LockFile <i>filename</i>	(logs/accept.lock)	C c
ScoreBoardFile <i>file</i>	(logs/apache_status)	C c
ServerAdmin <i>email-addr</i>		C cv
ServerType { <i>inetd</i> <i>standalone</i> }	(standalone)	C c
ServerName <i>name</i>	(<i>determined automatically</i>)	C cv
ServerAlias <i>fqdn</i> ...		C v
ServerSignature { <i>On</i> <i>Off</i> <i>Email</i> }	(<i>Off</i>)	C cvda 
ServerPath <i>pathname</i>		C v
ServerTokens { <i>Min</i> <i>imal</i> <i>OS</i> <i>Full</i> }	(<i>Full</i>)	C c 
BindAddress { <i>*IP-addr</i> <i>fqdn</i> }	(<i>*</i>)	C c
Listen [<i>IP-addr</i>]: <i>port-number</i>		C c
Port <i>portno</i>	(80)	C c
User { <i>username</i> <i>#userid</i> }	(<i>#1</i>)	C cv
Group { <i>group-name</i> <i>#group-id</i> }	(<i>#1</i>)	C cv
NameVirtualHost <i>addr</i> [: <i>port</i>]		C c 
UseCanonicalName { <i>On</i> <i>Off</i> }	(<i>On</i>)	C cvda 
CoreDumpDirectory <i>directory</i>	(<i>as ServerRoot</i>)	C c 
IdentityCheck { <i>On</i> <i>Off</i> }	(<i>Off</i>)	C cvd

```
ClearModuleList C c
AddModule module ... C c
AddModuleInfo module text E cv 
ExtendedStatus {On|Off} (Off) E c 
```



Sectional directives

```
<Directory {pattern | ~ regex} > ... </Directory> C cv 
<DirectoryMatch regex> ... </DirectoryMatch> C cv 
<Files {pattern|~ regex} > ... </Files> C cvda 
<FilesMatch regex> ... </FilesMatch> C cvda 
<Location {pattern|~ regex} > ... </Location> C cv 
<LocationMatch regex> ... </LocationMatch> C cv 
<VirtualHost pattern> ... </VirtualHost> C c
<IfDefine [!]parameter> ... </IfDefine> C cvda 
<IfModule [!]module> ... </IfModule> C cvda
<Limit method> ... </Limit> C cvda
<LimitExcept method> ... </LimitExcept> C cvda
```


Logging directives







```
ErrorLog {file|syslog[:facility]} (logs/error_log) C cv 
CustomLog file-or-pipe {format-string|format-name} B cv 
[env=[!]var]
TransferLog file-or-pipe (logs/access_log) B cv
HostNameLookups {On|Off|Double} (Off) C cvd 
RefererIgnore hostname ... E cv
LogFormat format-string ("%h %l %u %t \"%r\" %s %b") B cv 
[format-name]
LogLevel {emerg|alert|crit|error|warn|notice|info|debug} (error) C cv 
```

format-string can contain literal text and format specifiers:







```
%a Remote IP address
%b Number of bytes sent (excluding headers)
%{var}e Environment variable value
%f Filename
%h Remote host
%{hdr}i Incoming header value
%l Remote logname (from identd)
%{label}n Labelled note from another module 
%{hdr}o Outgoing header value
%p Canonical port number of server
%P Process ID of child server process
%r First line of request
%s Status
%t Time in Common Log Format (CLF) format
%{format}t Time (format is strftime format)
%T Time taken to serve the request (in seconds)
%u Remote username
%U URL requested
%V Canonical ServerName of server
%V Server name as per UseCanonicalName setting 
```

Performance tuning directives








```
Timeout secs (300) C c
KeepAlive {On|Off} (On) C c
KeepAliveTimeout seconds (15) C c
MaxKeepAliveRequests number (100) C c
MaxClients number (256) C c
MaxRequestsPerChild number C c
ExcessRequestsPerChild number E c 
MaxSpareServers number (10) C c
```

```
MinSpareServers number (5) C c
StartServers number (5) C c
ListenBacklog number (511) C c 
LimitRequestBody nbytes C cvda 
LimitRequestFields number (100) C c 
LimitRequestFieldSize nbytes (8190) C c 
LimitRequestLine nbytes (8190) C c 
SendBufferSize bytes C c
RLimitCPU {secs|max} [{secs|max}] C cvda
RLimitMEM {bytes|max} [{bytes|max}] C cvda
RLimitNPROC {nprocs|max} [{nprocs|max}] C cvda
ThreadsPerChild number (50) C c 
```

File typing directives

```
DefaultType MIME-type (text/html) C cvda
ForceType MIME-type B da
AddEncoding MIME-encoding extension ... B cvda
AddLanguage MIME-language extension ... B cvda
AddType MIME-type extension ... B cvda
DefaultLanguage MIME-language (no default language) C cvda 
LanguagePriority MIME-language ... B cvda
XBITHack {On|Off|Full} (Off) B cvda
MetaFiles {On|Off} (Off) E cvda 
MetaDir dir-name (.web) E cvda 
MetaSuffix suffix (.meta) E cvda 
MimeMagicFile filename E cv 
ContentDigest {On|Off} (Off) C cvda 
ExpiresActive {On|Off} E cvda
ExpiresByType MIME-type expiry-code E cvda
ExpiresDefault expiry-code E cvda
Header {set|append|add|unset} header value E cvda
```

Mapping directives

```
Action {MIME-type|handler-name} script B cvda
Alias url-path real-path B cv
AliasMatch url-regex path-replacement B cv 
ErrorDocument error-code {string|url} C cvda
UserDir {directory|DISABLED [user ...]} (public_html) B cv 
ENABLED user ...
Redirect [status] url-path url B cvda
RedirectMatch [status] url-regex dest-url B cv 
RedirectPermanent url-path url-dest B cvda
RedirectTemp url-path url-dest B cvda
Script method script B cvd
ScriptAlias url-path script-dir B cv
ScriptAliasMatch url-regex script-dir B cv 
AddHandler handler-name extension ... B cvda
RemoveHandler extension ... B da 
SetHandler handler-name B da
ImapBase {map|referer|url} (http://server) B cvda
ImapDefault {error|nocontent|referer|menu (nocontent)} B cvda
[url]
ImapMenu {none|formatted|semiformatted|unformatted} B cvda
RewriteBase url E cvda
RewriteCond test-string cond-pattern [flags] E cvda
RewriteEngine {On|Off} (Off) E cvda 
RewriteLock filename E cv 
RewriteLog filename E cv
RewriteLogLevel digit E cv
```

```
RewriteMap map-name map-type:map-source
RewriteOptions option
RewriteRule pattern substitution [flags]
```

Scripting directives

```
BrowserMatch regexp var[=value] ...
BrowserMatchNoCase regexp var[=value] ...
PassEnv varname ...
SetEnv varname value
SetEnvIf attribute regex var[=value] ...
SetEnvIfNoCase attribute regex var[=value] ...
UnsetEnv varname ...
ScriptLog filename
ScriptLogBuffer size-bytes (1024)
ScriptLogLength length-bytes (10385760)
```

Directory indexing directives

```
DirectoryIndex file ... (index.html)
ReadmeName filename
HeaderName filename
IndexIgnore pattern ...
IndexOrderDefault {Ascending|Descending} {Name|Date|
    Size|Description}
DefaultIcon url
AddAlt "string" file ...
AddAltByEncoding "string" MIME-encoding ...
AddAltByType "string" MIME-type ...
AddIcon icon file ...
AddIconByType icon MIME-type ...
AddIconByEncoding icon MIME-encoding ...
AddDescription "description" file-pattern
IndexOptions {+option|-option} ... (no options)
```

Valid index options are: FancyIndexing, IconsHeight=pixels, IconsWidth=pixels, NameWidth=n, IconsAreLinks, ScanHTMLTitles, SuppressColumnSorting, SuppressDescription, SuppressHTMLPreamble, SuppressLastModified, SuppressSize

Access control directives

```
AccessFileName filename ... (.htaccess)
AllowOverride directive-group ... (All)
```

Valid directive groups are: None, All, AuthConfig, FileInfo, Indexes, Limit, Options

```
Options {+feature|-feature} ... (All)
```

Valid options are: None, All, ExecCGI, FollowSymLinks, Includes, IncludesNOEXEC, Indexes, MultiViews, SymLinksIfOwnerMatch

```
AuthName realm-name
AuthType type
AuthUserFile filename
AuthGroupFile filename
AuthAuthoritative {On|Off} (On)
allow from {all|host ...|env=var}
deny from {all|host ...|env=var}
order {allow,deny|deny,allow|
    mutual-failure} (deny,allow)
Require {user user ...|group group ...|valid-user}
Satisfy {All|Any} (All)
```

```
E cv Proxy/cache directives
E cvda NoProxy {host|domain|ip-addr|subnet} ...
E cvda AllowCONNECT port ... (443 563)
ProxyBlock {*|host|domain} ...
ProxyDomain domain-name
ProxyPass path url
ProxyPassReverse path url
ProxyReceiveBufferSize number-bytes
ProxyRemote match remote-server
ProxyRequests {On|Off} (Off)
ProxyVia {On|Off|Full|Block} (Off)
CacheDefaultExpire hours (1)
CacheDirLength number (1)
CacheDirLevels number (3)
CacheForceCompletion percentage-complete (90)
CacheGcInterval hours
CacheLastModifiedFactor factor (0.1)
CacheMaxExpire hours (24)
CacheRoot directory
CacheSize kb (5)
NoCache {*|host|domain} ...
```

Common Gateway Interface (CGI) variables

```
AUTH_TYPE Authentication method used
CONTENT_LENGTH Length of input stream data
CONTENT_TYPE Internet media type of input stream
GATEWAY_INTERFACE CGI version
PATH_INFO URL part after script identifier
PATH_TRANSLATED PATH_INFO translated into filesystem
QUERY_STRING Query string from URL (if present)
REMOTE_ADDR IP address of client
REMOTE_HOST DNS name of client
REMOTE_IDENT Remote user id (unreliable)
REMOTE_USER Name of the authenticated user
REQUEST_METHOD HTTP request method
SCRIPT_NAME Virtual path of the script
SERVER_NAME Host-name of the server
SERVER_PORT Port number of server
SERVER_PROTOCOL Name and version of the protocol
SERVER_SOFTWARE Server software name and version
HTTP_ACCEPT MIME types the browser will accept
HTTP_REFERER URL of referring document
HTTP_USER_AGENT Client software identification
MOD_PERL Defined if running under mod_perl
```

Server Side Includes (SSI)

Format is: <!--#element attr=value ... -->

Elements are:

```
config controls parsing; attributes: errmsg, sizefmt (one of
bytes or abbrev), timefmt (strftime format)
echo print the value of a variable; attribute var (can be
a CGI variable or one of: DATE_GMT, DATE_LOCAL,
DOCUMENT_NAME, DOCUMENT_URI or LAST_MODIFIED)
set set the value of a variable; attributes: var, value
printenv print a list of all variables and their values
exec execute a shell command or CGI script; attribute: cmd
or cgi (IncludesNOEXEC option disables exec)
fsize print size of file; attribute: file or virtual
flastmod print file modification time; attribute file or virtual
```

```
include include another document; attribute file or virtual
if conditional; attribute: expr
elif conditional; attribute: expr
else conditional
endif conditional
```

HTTP 1.1 status codes

```
100 Continue 404 Not found
101 Switching protocols 405 Method not allowed
200 OK 406 Not acceptable
201 Created 407 Proxy authentication required
202 Accepted 408 Request timeout
203 Non-authoritative information 409 Conflict
204 No content 410 Gone
205 Reset content 411 Length required
206 Partial content 412 Precondition failed
300 Multiple choices 413 Request entity too large
301 Moved permanently 414 Request-URI too long
302 Moved temporarily 415 Unsupported media type
303 See other 500 Internal server error
304 Not modified 501 Not implemented
305 Use proxy 502 Bad gateway
400 Bad request 503 Service unavailable
401 Unauthorized 504 Gateway timeout
402 Payment required 505 HTTP version not supported
403 Forbidden
```

Apache Web Resources

<http://www.apache.org> Apache home page
<http://modules.apache.org> Apache Module Registry
<http://www.apache-ssl.org> Apache-SSL home page
<http://www.modssl.org> mod_ssl home page
<http://java.apache.org> The Java-Apache Project
<http://perl.apache.org> The Apache/Perl Integration Project
<http://www.php.net> PHP: Hypertext Processor
<http://www.apacheweek.com> Apache Week
<http://www.netcraft.com/survey> Netcraft Server Survey
<http://www.refcards.com> Quick Reference Cards

Apache Quick Reference Card

A **refcards.com**™ quick reference card.
Revision 1.6 for Apache version 1.3.6 [May 1999]
Published by Ford & Mason Ltd.
© 1998, 1999 Ford & Mason Ltd. All rights reserved.
Permission is granted to print and duplicate this card for personal or individual, internal business use. Copies of this card (& others) can be ordered through our web site: <http://www.refcards.com>, which also has versions available for downloading.
Please send feedback to: feedback@refcards.com
refcards.com is a trademark of Ford & Mason Ltd.
The Apache feather is used with permission of the Apache Group.